







00600A2NANA017

Adapter

10GHz 50Ω Quick N(M)-SMA(F)Adapter/Nickel

Features



High Repeatability



Low VSWR

Electrical Specifications

Frequency	DC-10GHz
VSWR	1.3:1(Max.)
Impedance	50Ohm
Connection 1	Quick N Male
Connection 2	SMA Female

Mechanical


Environmental

Operating Temperature -40	°C~85°C
---------------------------	---------

Material

Part	Material	Plated
Body	Brass	Nickel
Center Pin	Phosphor Bronze	Gold
Insulator	Teflon	

Outling Drawing (Unit:mm) Tolerance:±0.1mm







Test Report

2.00 511 5	SWR 0.100U/						=		S22 LogN	4 10.00dB/ 0.00						
		1:		00000			.0229	50.00		1			000 GH		38.51	
1.90		2:		00000			.0684	40.00		2			000 GH		31.39	
1.80	_	3:		00000			0419	30.00	+	3			000 GH		35.16	
1.70		4:		00000			1563	20.00		4			000 GH		22.50	3 d
1.60		> 5:	10.0	00000	GHz	1.	1768	10.00		> 5	: 1	10.0000	000 GH	2 -	19.64	4 c
1.50								0.00								
1.40					-		-	-10.00	+	+	\pm	\pm				
1.30	_	+	\vdash	-	_	_	-	-20.00	+	+	+	_				-
1.20								-30.00	\perp		_		4			
1.10				man	-		MANA	40.00		2						
1.00	WWW 2		. Nach					5000	1							
>Ch1: Start 10	0.000 MHz —	3~	,			Stop 10	0000 GHz		art 100.00	0 MHz —	_	_		9	top 10.00	000
>Ch1: Start 10	0.000 MHz —		V8			Stop 10	0000 GHz		art 100.00	0 MHz —				S	top 10.00	000
>Ch1: Start 10	\$21 LogM 1.0		0.68		_	Stop 10	0000 GHz		art 100.00			1.0000	00 GHz			
>Ch1: Start 10	0.000 MHz —		148			Stop 10	0000 GHz		art 100.00	0 MHz — 1: 2:			00 GHz	- ¢.	09123	3 d
>Ch1: Start 10	0.000 MHz —		0.88			Stop 10	0000 GHz		art 100.00	1:		2.4000		-0. -0.	09123	d d
5.00 Tr 3	0.000 MHz —		0.68			Stop 10	0000 GHz		at 100.00	1: 2:		2.4000 3.5000	00 GHz 00 GHz	-0. -0. -0.	09123 14648 1679 1	3 d 3 d
5.00 4.00 3.00 2.00	0.000 MHz —		0.8			Stop 10	0000 GHz		at 100.00	1: 2: 3:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d
5.00 Tr 3	0.000 MHz —		0.8			Stop 10	0000 GHz		at 100.00	1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz	-0. -0. -0.	09123 14648 1679 1	3 d 3 d 1 d
5.00 4.00 3.00 2.00	0.000 MHz —		3.68				0000 GHz			1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d
5.00 Tr 3 4.00 2.00 1.00	10.000 MHz — S21 LogM 1.0		3/8	2 2		Stop 10	0000 GHz		art 100.00	1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d
5.00 4.00 3.00 2.00 1.00 1.00 1.00	10.000 MHz — S21 LogM 1.0		0.68	2			0000 GHz			1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d
500 7: 3 500 4.00 3.00 2.00 1.00 -1.00	10.000 MHz — S21 LogM 1.0		0.48	2			0000 GHz			1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d
5.00 4.00 3.00 2.00 1.00 1.00 1.00	10.000 MHz — S21 LogM 1.0		338	2			0000 GHz			1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d 2 d
500 7: 3 500 4.00 3.00 2.00 1.00 -1.00	10.000 MHz — S21 LogM 1.0		3.48	2			0000 GHz			1: 2: 3: 4:		2.4000 3.5000 5.8000	00 GHz 00 GHz 00 GHz	-0. -0. -0.	09123 14648 16791 22012	3 d 3 d 1 d 2 d

All Specification Changed Without Notification.