




90193-F30383-G

Testing Probe

8GHz 50Ω IP I(M)/Gold- SMA(F)/Stainless 2Hole Flange Probe Adapter

Features


- High Repeatability
- Low VSWR



Test Report

Electrical Specifications

Frequency	DC-8GHz
VSWR	DC-3GHz: 1.25:1(Max.) 3-6GHz: 1.4:1(Max.) 6-8GHz: 1.6:1(Max.)
Insertion Loss	0.5dB(Max.)@DC-3GHz 0.8dB(Max.)@3-8GHz
Impedance	50Ohm
Connection 1	SMA Female
Connection 2	IP I Male



Mechanical

Durability	IP I: 100K Cycles (Min.) SMA: 500Cycles (Min.)
Spring Force	Signal Conductor: 35gf±15gf~220gf±15gf@0~3.8mm Ground: 45gf±15gf~200gf±15gf@0~3.8mm

Environmental

Operating Temperature	-40°C~85°C
-----------------------	------------


Note.

- 測試數據為實驗室測試值
- 產品使用壽命受使用環境、公差等因素影響，實際使用壽命以客戶端測試使用狀況為主


Material

Part	Material	Plated
IP Body	Brass	Nickel
Center Pin	Brass	Gold
Insulator	Teflon	
Spring	SWP	Nickel
Center Pin	Brass	Gold
SMA Body	Stainless Steel	

I-PEX 20279-001 Size



Outling Drawing (Unit:mm)



All Specification Changed Without Notification.